



TECHNICAL DATA

PRO-GEAR 75W-80 SS

Semi-synthetic manual transmission fluid with multiple applications

Product code: OLF75EP

Product Description:

PRO-GEAR 75W-80 SS is a premium semi-synthetic manual transmission fluid recommended for use in a wide range of passenger cars and vans on the road today.

PRO-GEAR 75W-80 SS exceeds the performance levels of more conventional API GL-4/GL-5 lubricants in terms of synchroniser performance, thermal and oxidative stability, shift quality and fuel efficiency. In addition, PRO-GEAR 75W-80 SS allows considerable rationalisation for out of warranty service fill by being able to replace OEM genuine oils.

Benefits:

- Improved synchromesh performance
- Improved shift quality
- Thermal and oxidative stability
- Load carrying and hardware durability
- Pitting resistance
- Shear stability
- Low temperature shift feel
- Seal compatibility
- Corrosion protection

Applications:

PRO-GEAR 75W-80 SS is recommended for use in a wide variety of manual transmissions in passenger cars and vans that are out of vehicle warranty where an SAE 75W-80 viscosity grade is required.

BMW	ü	CITROEN	ü	ALFA ROMEO	ü	VOLKSWAGEN	ü
MINI	ü	PEUGEOT	ü	FIAT	ü	SEAT	ü
MERCEDES	ü	RENAULT	ü	VOLVO	ü	SKODA	ü
SMART	ü	DACIA	ü	HONDA	ü	VAUXHALL	ü

PRO-GEAR 75W-80 SS is recommended where the specification MTF-94 is called for.

Product Specification:



TECHNICAL DATA

API	GL-4, GL-5
-----	------------

Typical Test Data:

Appearance	Clear yellow liquid
Density @ 20°C	0.875
Kinematic Viscosity @ 100°C (cSt)	9.1
Kinematic Viscosity @ 40°C (cSt)	58.0
Viscosity Index	136
Flash Point (COC, °C)	220
Pour Point (°C)	-45

Health & Safety:

Please refer to the safety data sheet, a copy of which is freely available to all of our customers.