

TECHNICAL DATA

PRO-GEAR 75W-80 FS

Fully synthetic manual transmission fluid

Product code: OLF75FSP

Product Description:

PRO-GEAR 75W-80 FS is a premium quality fully synthetic manual transmission fluid recommended for use in a wide range of passenger cars and light duty commercial vehicles. It exceeds the performance levels of more conventional API GL-4/GL-5 lubricants in terms of synchroniser performance, thermal and oxidative stability, shift quality and fuel efficiency. PRO-GEAR 75W-80 FS is formulated with premium base oils and advanced additive technology to ensure component durability over extended periods.

Benefits:

- Improved shift quality
- Thermal and oxidative stability
- Pitting resistance
- Shear stability
- Excellent low temperature performance
- Seal compatibility
- Corrosion protection

Application:

PRO-GEAR 75W-80 FS is recommended for use in a wide variety of manual transmissions in passenger cars and light duty commercial vehicles. In particular, it can be used where any of the following specifications are required.

Product Specification:

API	GL-4, GL-5
BMW	MTF LT-2 / LT-3 / LT-4
Fiat	MZ1 / MZ6
Ford	WSD-M2C200-C / WSS-M2C200-D2
GM	GM 1940182 / 1940764 / 1940768 / 1940004 / 19529104
Honda	Special Honda MTF / MTF-II / MTF-III
Nissan	MT-XZ / MT-XZ TL (JR Type)
PSA	B71 2330
Volvo	97308 / 97309
VW	G 009 317 / 052 171 / 052 178 / 052 512 / 052 726 / 060 726, G 50, GO 52
	527 A2 / 70 726 A2

PRO-GEAR 75W-80 FS is recommended where Special Gear Oil MTF 94 was originally required.



TECHNICAL DATA

Typical Test Data:

Appearance	Clear & Bright
Density @ 20°C	0.877
Kinematic Viscosity @ 100°C	9.5
(cSt)	
Kinematic Viscosity @ 40°C	54.0
(cSt)	
Viscosity Index	161
Flash Point (COC, °C)	215
Pour Point (°C)	-45

Health & Safety:

Please refer to the safety data sheet, a copy of which is freely available to all of our customers.