



# TECHNICAL DATA

## ANTIFREEZE LONGLIFE RED

Ethylene glycol based OAT antifreeze

Product code: OLFRD

### Product Description :

ANTIFREEZE LONGLIFE RED is blended from an ethylene glycol based engine coolant concentrate, which uses Organic Acid Inhibitor Technology and is free from nitrites, amines, phosphates, borates and silicates. It is BTC Classification Type 4E.

Fleet trials have shown that when used at the correct concentration coolants based on Organic Acid Inhibitor Technology continue to provide effective corrosion protection for up to 250,000km for passenger cars and 500,000km in commercial vehicles. It is recommended that the coolant is replaced when the above mileages have been reached or after 5 years. ANTIFREEZE LONGLIFE RED provides excellent protection to engine cooling systems, whether they are predominantly of ferrous or aluminium construction. Unlike traditional coolants which employ inorganic inhibitors, ANTIFREEZE LONGLIFE RED has excellent hard water stability and very low inhibitor depletion rates.

### Application:

ANTIFREEZE LONGLIFE RED is suitable for all year round usage in automotive and commercial petrol and diesel engines and certain industrial applications.

### Recommended Dilutions:

**ANTIFREEZE LONGLIFE RED can be used as supplied, or further diluted in accordance with the table below.**

Concentration (by volume)	50%	80%	100%
Freeze Protection (°C)*	- 20	- 38	- 56

\*Average of freezing point and pour point.

### Product Specification:

**ANTIFREEZE LONGLIFE RED meets the requirements of the following European & international standards:**

ASTM D 3306	ASTM D 4985	SAE J 1034	BS 6580: 2010
JIS K 2234 *			
AFNOR NF R15-601 *	FFV Heft R443	CUNA NC 956-16	UNE 26361-88
NATO S 759			

\* with the exception of reserve alkalinity

**ANTIFREEZE LONGLIFE RED meets the requirements of the following OEM specifications:**

Volvo VCS Coolant	Chrysler MS 9176	Cummins 85T8-2 & 90T8-4
-------------------	------------------	-------------------------



# TECHNICAL DATA

Leyland Trucks LTS 22 AF 10      Mack 014GS 17004      MAN 248, 324 (SNF) & B&W  
D 36 5600  
Mercedes MB 325.3      Renault 41-01-001      VAG TL 774 D/F  
GM 1899 M, US 6277 M & OPEL GM QL130100      John Deere H 24 B1 & C1  
MTU MTL 5048      Ford ESE M97B49-A, WSS-M97B44-D & ESD M97B49-A

ANTIFREEZE LONGLIFE RED can be used where Glysantin® G12, G12+, G30, G33 or G34 were originally recommended.