

TECHNICAL DATA

C5 0W-20 VOL LS

Fully synthetic, low SAPS fuel efficient engine oil

Product code: OLFVO

Product Description:

C5 0W-20 VOL LS is a premium quality fully synthetic low SAPS engine oil which, as a result of its specialised formulation and low viscosity, provides significant fuel saving benefits to the motorist. C5 0W-20 VOL LS also possesses exceptional low temperature characteristics meaning that the oil circulates quickly even in the most demanding cold start conditions.

Benefits:

- Provides significant reductions in fuel consumption
- Excellent low temperature fluidity
- High thermal stability
- Outstanding wear protection
- Fully synthetic low SAPS formulation

Applications:

C5 0W-20 VOL LS is recommended for many of the latest petrol and diesel engines in Volvo cars as well as, for example, Hyundai, Honda, Toyota, Mazda and Suzuki when one of the following specifications is stated by the vehicle manufacturer along with a SAE 0W-20 viscosity grade.

Product Specification:

ACEA	C5
API	SN
Volvo	VCC RBS0-2AE

Typical Test Data:

Kinematic Viscosity @ 100°C (cSt)	9.0
Kinematic Viscosity @ 40°C (cSt)	47.0
Viscosity Index	176
Flash Point (COC, °C)	>200
TBN (mg KOH/g)	8.0
Sulphated Ash (% wt)	0.80
Pour Point (°C)	-48



Health & Safety:

Please refer to the safety data sheet, a copy of which is freely available to all of our customers.

20 VOL LS